

PART NO.**I.D.**

| | |
|-------|--------|
| FS-04 | 1/4" |
| FS-06 | 3/8" |
| FS-08 | 1/2" |
| FS-10 | 5/8" |
| FS-12 | 3/4" |
| FS-16 | 1" |
| FS-20 | 1-1/4" |
| FS-24 | 1-1/2" |



(Available in Silver and Black)

Firesleeve is made from a high bulk fiberglass material that is then braided to make a hollow sleeve. This technique allows the finished coated product "give," and be slightly expandable where and when necessary. It is coated with a thick coating of iron oxide (FeO) silicone rubber. This product is rated for 500° (260°C) of continuous exposure. Product can be used for short periods of time at higher temperature ratings, (2000°F for 15-20 minutes and 3000°F to 15-31 sec). Product is highly impervious to most liquids, this includes those that are hydro carbon based. And retains its functionality even after being under water for more than 12 hrs. Fire Sleeve may be installed over a wide variety of items and materials. A few such items would be hoses, cables, tubing and or pipes. Due to its capabilities, it is a good choice for use where you might be exposed to items such as, molten metal, radiant heat, abrasive surfaces, corrosive materials and liquids and electrical. Our Fire Sleeve is available in the following sizes: 1/4", 3/8", 1/2", 5/8", 3/4", 1", 1-1/4", and 1-1/2".